

CBE/CBE-A

后拉定位式橡胶筒夹夹头

后拉定位式


- 后拉夹持，配合挡料块机构，可精准定位工件入料长度，使长度精度控制更加精准。
- 挡料块与防尘盖可互换搭配使用，应用与防屑功能可以兼顾。
- **J**值为连结螺帽末车制螺牙时的孔径。
- **K max**值为连结螺帽可车制螺牙之最大规格，可依实际需求订制。



規格

型号	套筒行程 (mm)	最大夹持能力 圆棒 (mm)	最大夹持能力 六角材 (mm)	最大夹持能力 方材 (mm)	容许最大入力 kN(kgf)	最大夹持力 kN(kgf)	最高回转数 min ⁻¹ (r.p.m.)	重量 (kg)	使用筒夹	适用回转缸	最大使用压力 (kgf/cm ²)
CBE-42	4.5	4~42	7~30	7~36	34.3(3500)	78.4(8000)	7000	6	RG-42	TK-B846	2.8(28)
CBE-4212	4.5	4~42	7~30	7~36	34.3(3500)	78.4(8000)	7000	6	RG-42	TK-B846	2.8(28)
CBE-42A5	4.5	4~42	7~30	7~36	34.3(3500)	78.4(8000)	7000	6.3	RG-42	TK-B846	2.8(28)
CBE-42A6	4.5	4~42	7~30	7~36	34.3(3500)	78.4(8000)	7000	7.4	RG-42	TK-B846	2.8(28)
CBE-52	4.5	4~52	7~30	7~36	39.2(4000)	92.1(9400)	7000	6.9	RG-52	TK-A853	3.2(32)
CBE-5212	4.5	4~52	7~30	7~36	39.2(4000)	92.1(9400)	7000	6.7	RG-52	TK-A853	3.2(32)
CBE-5217	4.5	4~52	7~30	7~36	39.2(4000)	92.1(9400)	7000	8.9	RG-52	TK-A853	3.2(32)
CBE-52A5	4.5	4~52	7~30	7~36	39.2(4000)	92.1(9400)	7000	7.8	RG-52	TK-A853	3.2(32)
CBE-52A6	4.5	4~52	7~30	7~36	39.2(4000)	92.1(9400)	7000	8.3	RG-52	TK-A853	3.2(32)
CBE-65	4.5	4~65	8~46	8~56	44.1(4500)	103(10500)	6000	9.3	RG-65	TK-1068	3.0(30)
CBE-6517	4.5	4~65	8~46	8~56	44.1(4500)	103(10500)	6000	8.6	RG-65	TK-1068	3.0(30)
CBE-65A5	4.5	4~65	8~46	8~56	44.1(4500)	103(10500)	6000	10.8	RG-65	TK-1068	3.0(30)
CBE-65A6	4.5	4~65	8~46	8~56	44.1(4500)	103(10500)	6000	9.5	RG-65	TK-1068	3.0(30)
CBE-65A8	4.5	4~65	8~46	8~56	44.1(4500)	103(10500)	6000	9.5	RG-65	TK-1068	3.0(30)

尺寸



保留规格修改的权利

型号	-	A	A1	A2	B	C(H6)	D	D1	E	E1	F	G max.	G min.	H	J	K max.	L	L1	M
CBE-42	-	150	132	100	95	140	104.8	-	5	20	48	22.5	18	17	45	M55x2	4~M10x25	19.5	58
CBE-4212	-	132	132	100	95	120	100	-	5	-	48	22.5	18	17	45	M55x2	4~M10x25	19.5	58
CBE-42	A5	132	132	100	105	-	104.8	82.56	-	-	48	37.5	33	17	45	M55x2	4~M10x30	16	68
CBE-42	A6	160	132	100	105	-	133.4	106.38	-	35	48	37.5	33	17	45	M55x2	4~M12x35	18	68
CBE-52	-	150	140	107	99	140	104.8	-	5	-	52	22.5	18	17	56	M60x2	4~M10x20	14.5	60
CBE-5212	-	140	140	107	99	120	100	-	5	-	52	22.5	18	17	56	M60x2	4~M10x20	14.5	60
CBE-5217	-	180	140	107	109	170	133.4	-	6	-	52	31.5	27	17	56	M60x2	4~M12x30	18	70
CBE-52	A5	140	140	107	109	-	104.8	82.56	-	-	52	37.5	33	17	56	M60x2	4~M10x30	16	70
CBE-52	A6	160	140	107	109	-	133.4	106.37	-	-	52	37.5	33	17	56	M60x2	4~M12x35	18	70
CBE-65	-	157	157	122	116	140	104.8	-	6	-	56	34.5	30	17.5	68	M75x2	4~M10x30	18	74
CBE-6517	-	180	157	122	114	170	133.4	-	6	24	56	32.5	28	17.5	68	M75x2	4~M12x30	18	72
CBE-65	A5	157	157	122	114	-	104.8	82.56	-	-	56	38.5	34	17.5	68	M75x2	4~M10x25	16	72
CBE-65	A6	157	157	122	112	-	133.4	106.38	-	-	56	36.5	32	17.5	68	M75x2	4~M12x35	18.5	70
CBE-65	A8	202	157	122	116	-	171.4	139.72	-	38	56	36.5	32	17.5	68	M75x2	4~M16x35	24	74